



The Racklight is a slim luminaire specially designed to pack maximum power into a minimum of space. Manufactured in an anodised and sealed aluminium body, it can withstand any harsh environment and has a longer luminous flux life than most luminaires on the market.

Quick and easy Anodised Alu to install Best cooling DIM 0-10V DALI IP66 IK06 180 **-** 277VAC (50-60Hz) 2,2 - 3,3 $\mu mol/J$ Angle 21 - 132 120° wide μmol/s



In indoor vertical farms, the constrained environment is the same as in industry. That's why VGD has designed an ultra-slim luminaire that is IP66 waterproof and can deliver up to 80W per LED rigid bar to increase crop density. Installation is simple because all the electrical connections are made using IP68 waterproof connectors that can be screwed on without the need for tools, so you can design a kit to suit your needs and perfectly control the homogeneity and photons emitted. The remote use of drivers reduces heat emission into the room by 38% and ensures a completely safe low-voltage DC48V installation. This makes it ideal for 24-hour production.

Power		10-40 Watts	
Size (mm)		1100x56x33	
Input Voltage		180 - 277VAC (50-60Hz)	
THD		<14%	
Weight		0,870kg	
Power factor		> 0,94 at full load	
Angle		120°	
Efficiency		2,2 - 3,3 μmol/J	
PPF (360-760nm)		22 - 132 μmol/s	
IP & IK		66 / 06	
Lifetime Ta 25°C		40 000 hrs L80B10	
Spectral code		S4 - S5K - SSF- custom request available	
Warranty		3 years	
Certificates		CE, ENEC, ROHS, UL/CSA, RCM, PSE, EAC	
Dimming option		10 - 100%	
Market Car	Splitter output		Inox fixing hooks



view depends on options

- Spectrum adapted to each crop
- Guaranteed homogeneity
- · Compatible with pathogen testing
- Plug & Play, installation without tools
- Increases the rooting rate
- Ideal for growing shelves



VGD

396 Avenue Jean Baptiste Tron 13160 Chateaurenard France www.vgd-led.com contact@vgd-led.com +33 484 980 035